

DDR4 GAMING DELTA RGB

THE POWER FROM TEAM GROUP
T-FORCE | DELTA RGB
T-FORCE GAMING DDR4 DELTA RGB

Pursuing the perfect revolution

TEAM GROUP T-FORCE gaming series once again released the all new luminous memory module – DELTA RGB. The R on the heat spreader represents Revolution, and also stands for creative concept with an uncompromised spirit. The heat spreader is built with lighter, thinner and high quality metal material. The colorful light changes make the hollow "R" on the front even more stereoscopic, and echo the ultra wide angle luminous area. The extraordinary Revolution will provide players a new experience never seen before.

Full color, dazzling and 120° ultra wide angle force flow lighting effect

DELTA RGB is using full color, dazzling RGB LED lighting with force flow effect. Like a Jedi holding the lightsaber, players can be invincible in the gaming world. T-FORCE LOGO is like a warrior's badge, standing still in the changing lights. The full frame, 120° ultra wide angle luminous area at the top emits colorful light, and the light changes with the rhythm of the game, creating an unparalleled visual effect at night.



Asymmetric minimalist design

The one piece, geometric line design makes the heat spreader look simple but energetic, and the Cubist style in the new art movement is also presented, which is a perfect combination of technology and aesthetics. The embossed lines on the surface not only increase the heat dissipation area and also effectively enhance cooling of the memory module, so the quality of the operation can be finely stabilized.

T-FORCE DELTA RGB Gaming Memory Modules Supports Variety Kinds of Controlled Software

T-FORCE DELTA RGB memory module supports ASUS Aura Sync / GIGABYTE RGB Fusion 2.0 / MSI Mystic Light Sync / ASROCK-Polychrome Sync / BIOSTAR Advanced VIVID LED DJ software^[1]. These lightning controlled software allows gamers to control lighting effects and lighting synchronization with T-FORCE DELTA RGB luminous memory module. It creates a unique, dazzling color aesthetics and offers a brilliant RGB system!



[1] For more details about how to control the lighting effect by the software(ASUS Aura Sync / GIGABYTE RGB Fusion 2.0 / MSI Mystic Light Sync / ASROCK-Polychrome Sync// BIOSTAR Advanced VIVID LED DJ), please visit the official website of the software developer(ASUS/GIGABYTE/MSI/ASRock/BIOSTAR)



The transmitting performance can be greatly increased with JEDEC RC 2.0

Using the latest customized JEDEC RC 2.0 circuit board to increase the distance between the power layer and the signal layer. Compared to ordinary memories, the transmitting signal is raised by 35%. There will be no interference between the power and the signal, and gets better performance. It completely releases the transmission of memory module, and offers players the ultimate sensation of overclocking and a highly stable overclocking memory module.

XMP2.0 1 step overclocking technology

DELTA RGB series support Intel XMP 2.0. It is only one step away to experience the high speed sensation of overclocking.



Ultra low working voltage Save energy up to 40%

With low working voltage 1.2~1.4V from DDR4 DELTA RGB , it is not only energy saving but it can also reduce the temperature and the heat generated to offer the high speed running memory a stable and long time operation.

QVL approved by motherboard manufacturers

Multiple compatibility verifications with mainstream DDR4 motherboards to make sure its stability with all motherboards on the QVL(Qualified Vendor List). Therefore, you wouldn't have to worry about compatibility issues when purchasing high speed memory.



Main Feature

- Full frame 120° ultra wide angle lighting
- Built in Force Flow RGB lighting effect
- Aluminum alloy heat spreader with asymmetric minimalist design
- Supports ASUS Aura Sync software synchronization
- Latest JEDEC RC 2.0 PCB
- Energy saving 1.2V~1.4V ultra low working voltage
- Supports XMP2.0 one click overclocking technology
- QVL approved by all mainstream motherboard manufacturers



Specification

Module Type	DDR4 288 Pin Non-ECC Unbuffered DIMM								
Tested Speed	2666	2666	3000	3200	3200	3600	3600	4000	4000
Tested Latency	CL16-18-18-38	CL18-18-18-43	CL16-18-18-38	CL16-18-18-38	CL16-20-20-40	CL14-15-15-35	CL18-22-22-42	CL18-22-22-42	CL18-24-24-46
Capacity	8GB	32GB	8GB	8GB	8GB	8GBx2	8GB	8GBx2	16GBx2
	16GB	32GBx2	16GB	16GB	16GB	16GBx2	16GB		
	8GBx2		32GB	32GB	32GB		32GB		
	16GBx2		4GBx2	8GBx2	8GBx2		8GBx2		
Data transfer bandwidth			8GBx2	16GBx2	16GBx2		16GBx2		
			16GBx2	32GBx2	32GBx2		32GBx2		
			32GBx2						
Tested Voltage	1.2V	1.2V	1.35V	1.35V	1.35V	1.45V	1.35V	1.35V	1.4V
Dimensions	49(H) x 147(L) x 7(W)mm								
Warranty	Lifetime Warranty								



Ordering Information



Color	Frequency	CAS Latency/Voltage	Capacity	Team P/N
BLACK	DDR4-2666(PC4-21300)	CL16-18-18-38 1.2V	8GB	TF3D48G2666HC16C01
			16GB	TF3D416G2666HC16C01
		CL18-18-18-43 1.2V	32GB	TF3D432G2666HC18H01
	DDR4-3000(PC4-24000)	CL16-18-18-38 1.35V	8GB	TF3D48G3000HC16C01
			16GB	TF3D416G3000HC16C01
			32GB	TF3D432G3000HC16C01
	DDR4-3200(PC4-25600)	CL16-18-18-38 1.35V	8GB	TF3D48G3200HC16C01
			16GB	TF3D416G3200HC16C01
			32GB	TF3D432G3200HC16C01
		CL16-20-20-40 1.35V	8GB	TF3D48G3200HC16F01
			16GB	TF3D416G3200HC16F01
			32GB	TF3D432G3200HC16F01
	DDR4-3600(PC4-28800)	CL18-22-22-42 1.35V	8GB	TF3D48G3600HC18J01
			16GB	TF3D416G3600HC18J01
			32GB	TF3D432G3600HC18J01



Color	Frequency	CAS Latency/Voltage	Capacity	Team P/N
WHITE	DDR4-2666(PC4-21300)	CL16-18-18-38 1.2V	8GB	TF4D48G2666HC16C01
			16GB	TF4D416G2666HC16C01
		CL18-18-18-43 1.2V	32GB	TF4D432G2666HC18H01
	DDR4-3000(PC4-24000)	CL16-18-18-38 1.35V	8GB	TF4D48G3000HC16C01
			16GB	TF4D416G3000HC16C01
			32GB	TF4D432G3000HC16C01
	DDR4-3200(PC4-25600)	CL16-18-18-38 1.35V	8GB	TF4D48G3200HC16C01
			16GB	TF4D416G3200HC16C01
			32GB	TF4D432G3200HC16C01
		CL16-20-20-40 1.35V	8GB	TF4D48G3200HC16F01
			16GB	TF4D416G3200HC16F01
			32GB	TF4D432G3200HC16F01
	DDR4-3600(PC4-28800)	CL18-22-22-42 1.35V	8GB	TF4D48G3600HC18J01
			16GB	TF4D416G3600HC18J01
			32GB	TF4D432G3600HC18J01

Ordering Information



BLACK

Color	Frequency	CAS Latency/Voltage	Capacity	Team P/N
BLACK	DDR4-2666(PC4-21300)	CL16-18-18-38 1.2V	8GBx2	TF3D416G2666HC16CDC01
			16GBx2	TF3D432G2666HC16CDC01
		CL18-18-18-43 1.2V	32GBx2	TF3D464G2666HC18HDC01
	DDR4-3000(PC4-24000)	CL16-18-18-38 1.35V	4GBx2	TF3D48G3000HC16CDC01
			8GBx2	TF3D416G3000HC16CDC01
			16GBx2	TF3D432G3000HC16CDC01
			32GBx2	TF3D464G3000HC16CDC01
	DDR4-3200(PC4-25600)	CL16-18-18-38 1.35V	8GBx2	TF3D416G3200HC16CDC01
			16GBx2	TF3D432G3200HC16CDC01
			32GBx2	TF3D464G3200HC16CDC01
		CL16-20-20-40 1.35V	8GBx2	TF3D416G3200HC16FDC01
			16GBx2	TF3D432G3200HC16FDC01
			32GBx2	TF3D464G3200HC16FDC01
	DDR4-3600(PC4-28800)	CL14-15-15-35 1.45V	8GBx2	TF3D416G3600HC14CDC01
			16GBx2	TF3D432G3600HC14CDC01
		CL18-22-22-42 1.35V	8GBx2	TF3D416G3600HC18JDC01
			16GBx2	TF3D432G3600HC18JDC01
	DDR4-4000(PC4-32000)	CL18-22-22-42 1.35V	8GBx2	TF3D416G4000HC18JDC01
		CL18-24-24-46 1.4V	16GBx2	TF3D432G4000HC18LDC01

Ordering Information



WHITE

Color	Frequency	CAS Latency/Voltage	Capacity	Team P/N
WHITE	DDR4-2666(PC4-21300)	CL16-18-18-38 1.2V	8GBx2	TF4D416G2666HC16CDC01
			16GBx2	TF4D432G2666HC16CDC01
		CL18-18-18-43 1.2V	32GBx2	TF4D464G2666HC18HDC01
	DDR4-3000(PC4-24000)	CL16-18-18-38 1.35V	4GBx2	TF4D48G3000HC16CDC01
			8GBx2	TF4D416G3000HC16CDC01
			16GBx2	TF4D432G3000HC16CDC01
			32GBx2	TF4D464G3000HC16CDC01
	DDR4-3200(PC4-25600)	CL16-18-18-38 1.35V	8GBx2	TF4D416G3200HC16CDC01
			16GBx2	TF4D432G3200HC16CDC01
			32GBx2	TF4D464G3200HC16CDC01
		CL16-20-20-40 1.35V	8GBx2	TF4D416G3200HC16FDC01
			16GBx2	TF4D432G3200HC16FDC01
			32GBx2	TF4D464G3200HC16FDC01
	DDR4-3600(PC4-28800)	CL14-15-15-35 1.45V	8GBx2	TF4D416G3600HC14CDC01
			16GBx2	TF4D432G3600HC14CDC01
		CL18-22-22-42 1.35V	8GBx2	TF4D416G3600HC18JDC01
			16GBx2	TF4D432G3600HC18JDC01
			32GBx2	TF4D464G3600HC18JDC01
	DDR4-4000(PC4-32000)	CL18-22-22-42 1.35V	8GBx2	TF4D416G4000HC18JDC01
		CL18-24-24-46 1.4V	16GBx2	TF4D432G4000HC18LDC01

※ Above technical information is based on industry standard data and tested to be reliable. However, Team makes no warranty, either expressed or implied, as to its accuracy and assumes no liability in connection with the use of this product.

※ Team reserves the right to make changes in specifications at any time without prior notice.

※ Before purchasing memory products, please refer to the QVL(Qualified Vendor List) compatibility list first of the motherboard.

※ The quality of the CPU memory controller (IMC) and the version from the BIOS of motherboard may both potentially affect the operating frequency of the memory.